

Acetone

- Cleaning and Degreasing Agent -

Acetone is a dissolver and is used to clean tools from cured resins.
Furthermore is it used to degrease GRP-surfaces.

Features and Application Areas:

- neutral coloured
- smell is aromatic / fruity
- fully mixable with water
- light volatile
- boiling point at 56°C / melting point at -95°C
- dissolver for cleaning applications
- brush and equipment cleaner

Processing Information:

...cleaning the equipment:

brushes, lamination rolls, degassing rolls and other tools can be cleaned from non-cured epoxy or polyester resin with undiluted Acetone.

...cleaning the mould:

rub the mould or object with the help of cleaning rags. Let it air.

Information for the safe handling with hazardous substances:

Acetone is highly inflammable, irritating by inhalation and in contact with skin. Avoid contact with eyes. Keep out of the reach of children.

Storage / Disposal:

Store it at + 15°C up to 25°C.

Avoid release into the canalisation, into waters or into soil. Product left-overs are hazardous waste.

Further Information:

Do not hesitate to contact us. More custom-designed information can be ordered via telephone or you can find it on our web-site under 'product-info'.

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.

We recommend tests be performed for trials and suitability for the particular type of application.

With the newest printing of this data sheet the previous version loose validity!